

**Part #: 800060**

**Model 0000-140 with Manual C.A.F. Control System**  
**Retro-fit Compressed Air Foam System; does not include Chemical Injector**

**Performance**

CAFS Output	Two (2) 1-1/2" (38mm) outlets
Rated Capacity	1200 gpm (8:1 expansion ratio)
Maximum Pressure	150 psi

**General Specifications - Standard**

Plumbing	304 Stainless Steel Sched 40 Plumbing with Akron Valves.
----------	--

CAFS Outlets	Two (2) 1-1/2" (38mm) Outlets
Control Type:	Manual

Air Compressor	
Type:	Rotary Screw – PTO/Gear Driven
Output:	140 SCFM @ 125 psi
Maximum Pressure:	150 psi

**Dimensions**

Varies with Installation

**Please note that a chemical injector is not included with this system.**

**Part #: 800061**

**Model 0000-140 with Manual C.A.F. Control System**  
**Retro-fit Compressed Air Foam System; includes Chemical Injector**

**Performance**

CAFS Output	Two (2) 1-1/2" (38mm) outlets
Rated Capacity	1200 gpm (8:1 expansion ratio)
Maximum Pressure	150 psi

**General Specifications - Standard**

Plumbing	304 Stainless Steel Sched 40 Plumbing with Akron Valves.
----------	--

CAFS Outlets	Two (2) 1-1/2" (38mm) outlets
Control Type:	Manual

Air Compressor	
Type:	Rotary Screw – PTO/gear Driven
Output:	140 SCFM @ 125 psi
Maximum Pressure:	150 psi

**Chemical Injector**

Type:	Computerized – Class A Foam
Capacity:	850 gpm @ 0.2% 170 gpm @ 1.0%, 85 gpm @ 3.0%
Maximum Pressure:	400 psi 1.0 gpm @ 1200 psi
Application rate:	0.2 to 2.0 %

**Dimensions**

Varies with installation

**Part #: 800062**

**Model 0000-200 with Manual C.A.F. Control System**  
**Retro fit Compressed Air Foam System; does not include Chemical Injector**

**Performance**

CAFS Output	Two (2) 1-1/2" (38mm) outlets
Rated Capacity	1500 gpm @ 8:1 expansion ratio
Maximum Pressure	150 psi

**General Specifications - Standard**

Plumbing	304 Stainless Steel Sched 40 Plumbing, Akron Valves
----------	---

CAFS Outlets	Two (2) 1-1/2" (38mm) Outlets
Control Type:	Manual

Air Compressor	
Type:	Rotary Screw – PTO/Gear Driven
Output:	200 SCFM @ 125 psi
Maximum Pressure:	150psi

**Dimensions**

Varies with Installation

**Please note that a chemical injector is not included with this system.**

**Part #: 800063**

**Model 0000-200 with Manual C.A.F. Control System**  
**Retro-fit Compressed Air Foam system; includes Chemical injector**

**Performance**

CAFS Output	Two (2) 1-1/2" (38mm) outlets
Rated Capacity	1500 gpm @ 8:1 expansion ratio
Maximum Pressure	150 psi

**General Specifications - Standard**

Plumbing	304 Stainless Steel Sched 40 Plumbing with Akron Valves
----------	---

CAFS Outlets	Two (2) 1-1/2" (38mm) Outlets
Control Type:	Manual

Air Compressor	
Type:	Rotary Screw – PTO/Gear drive
Output:	200 SCFM @ 125 psi
Maximum Pressure:	150 psi

**Chemical Injector**

Type:	Computerized – Class A/B Foam Types
Capacity:	850 gpm @ 0.2% (170 gpm @ 1.0%, 85 gpm @ 3.0%)
Maximum Pressure:	400 psi
Application rate:	.02 to 1.0 %

**Dimensions**

Varies with Installation