



Green Acres Industries Inc.

PO Box 279 – Hwy 2 & Green Acres Rd.
Wawanesa, MB R0K 2G0

Ph 204 824 2392
Fax 204 824 2761

Date – June 7, 2008

2008 (GAI) Wildland Mini-Pumper Specifications

Chassis

- 2008 Ford F550 4-Door
- 6.4L Diesel
- Automatic Transmission
- 4 Wheel Drive
- Dual Alternators
- Air Conditioned
- 84” Cab to Axle
- 17’950 lb Gross Vehicle Weight Rating

Aluminum Body

- Aluminum Extruded Sub-frame (6061T6)
- Aluminum Body Compartments (5052 H32)
- Amdor Rollup Doors c/w In-cab Door-Ajar Warning
- U-Bolt Body-To-Chassis Frame Attachment
- Adjustable Compartment Shelving
- Rubber Floor & Shelve Tile

Whelen Emergency Lighting

- Halogen Lightbar w/ Alley Lights
- Rear Halogen Beacons
- Lower Level LED Flashers
- LED Ground Lights – Cab Ground Lights Turn on with Open door
- Siren System c/w 100 Watt Speaker

Scene Lights

- 12 volt – 150 Watt Extenda-lights
- 150 Watt Rear scene Lights

- Lightbar Alley Lights
- Remote Controlled SearchLight

Electrical

- ES-Key Multi-Plexed (Programmable) Electrical System
- Electrical System Allows For Remote Hook-up for Diagnostic or Trouble-Shooting Operations
- Function, Numerical & Color Coded Wiring Harness
- Sealed (Weather-Pack) Electrical Connectors

Snuffer CAFS System

- **2-Step** Fully Automatic Start-up Procedure
- 125 GPM x 60 SCFM Compressed Air System
- 34 HP Daihatsu Diesel Engine
- 1601 Foam-Pro Foam Proportioner
- Class1 Water & Foam Tank Level Gauges – Includes In-cab Remote Displays
- **One-Touch** Electronic Discharge Valves
- (2) – 1.50” Discharges
- (1) – 2.5” Draft Inlet
- (1) – 1.5” Hydrant-to-Tank Fill

Water & Foam Tanks

- 300 US Gal Co-Poly Water Tank
- 30 US Gal Co-Poly Foam Tank

MISC

- 10’ 500 lb Hydraulic MileMarker Winch
- Warn Stainless Steel Brush/Grille Guard
- Stainless Steel Tubular Cab Steps
- Flip-Down Rear Access Step

Hose Reel

- Electric Rewind Hose Reel c/w 150’ of 1 ½” Reeltex Hose